

2003 AFCEE Technology Transfer Workshop

Promoting Readiness through Environmental Stewardship

Bioremediation of MTBE Utilizing Permeable Reactive Barrier Technology

3-Year ESTCP Demonstration at Port Hueneme, CA

Karen Miller NFESC February 26, 2003




PRB Technology Overview

Treatment of MTBE-contaminated aquifers through:


- inoculation with MTBE-degrading organisms (MC-100 and SC-100)
- aeration/ oxygenation of the aquifer

Apply PRB technology to a mixed MTBE-BTEX dissolved plume






ESTCP Biobarrier Team





NBVC, Port Hueneme, CA







Demonstration System Design

- Treatment system must not alter the natural flow path
- Modular and flexible with respect to operating conditions.

Design:

- Close well spacing
- Injection at two depths
- Pulsed gas injection (air and O₂) [trapped gas continues to supplies oxygen for days after injection]







Features

Subsurface

PRB Subsurface Features

Monitoring wells O₂ delivery wells silt/sand 15 ft Shallow 20 ft K increases medium fine sand Deep ; 0.3 ft/d





Well Installation, August 2000













PRB Installation, August 2000




• 500 ft wide Biobarrier

- 252 air / O2 injection wells
- 174 monitoring wells









Microbial Inoculation




Seeded 165 feet of the BioBarrier with MTBE degrading cultures from Shell Global Solutions.








Dissolved Oxygen Distribution








Benzene Concentrations






MTBE Concentrations






TBA Concentrations





NBVC MTBE Plume Isoconcentration Contour, October 2002 (ug/L)





Final Remedy Options for NBVC





Operate P&T System / Remove Biobarrier System

O&M Costs:

- -FY02 O&M: \$225K/year
- -Life Cycle O&M /Life:

\$54M / 240 years

- Advantage:
 - -P&T at leading edge of plume
- Issues:
 - -High O&M/long service life
 - Disposes 1 million gallons to sanitary sewer annually
 - Est. 200 years to capture 200 gallons of MTBE between biobarrier and P&T






Remove P&T System / Operate Biobarrier System

- O&M Costs:
 - **-FY02 O&M:** \$75K/year
 - –Life Cycle O&M /Service:

\$3M / 40 years

- Advantage:
 - -Low O&M costs
 - -Complete mineralization of MTBE to CO₂ and water
- Issues:
 - -200 gallons of MTBE down gradient of biobarrier.
 - –Model predicted MTBE may discharge into surface waters.






Convert P&T System / Operate Biobarrier System

- O&M Costs:
 - **-FY02 O&M**: \$125K/year
 - -Life Cycle O&M / Life:

\$20M / 240 years

- Advantage:
 - –Completely contains MTBE plume
 - -Protects against future spills
 - No groundwater or other disposal costs
- Issues:

-P&T conversion: \$300K





Cost Savings

- Few cost-effective insitu remedies are known for MTBE impacted aquifers.
- The Navy spends \$10M a year operating and maintaining 24 P&T systems.
- Results from this project show that use of this technology at NBVC alone will lead to a cost savings of over \$30M.





Where's the demonstration going from here...

- MTBE and BTEX are being degraded to less than 5 ppb across width of the plume
- ESTCP demonstration ended Dec 2002.
- RAP accepted by the Los Angeles Regional Water Quality Control Board designated biobarrier technology as the final remedy for NBVC's MTBE plume

